

# 安徽艾约塔硅油有限公司

### IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

# 安徽省蚌埠市高新区兴中路 985 号

电话: 86-552-3827158 传真: 86-552-3822922

日月科技园

### TDS of Low Viscosity Silicone Oils IOTA PDMS 47V3-47V10

### Description

IOTA PDMS 47V3- 47V10 are a low viscosity polydimethylsiloxanic fluids.

### **Applications**

IOTA PDMS 47V3 - 47V10

47V3 for Chain Stopper for silicone polymerization;

47V10 for Lubricants (lubrication of elastomers or plastics on metal, on spandex agent);

Low temperature hydraulic fluids;

Thinning agents for RTV's and silicone sealants (Two component, room temperature vulcanizing silicone elastomers);

Coating additive to improve flowablity.

#### **Properties**

Very good heat stability,

Low surface tension,

High compressibility,

Excellent weathering resistance,

Good oxidation resistance,

Low freezing point,

Less change in viscosity as a function of temperature than non-silicone oils,

Good resistance to high and prolonged shear forces,

Low heat of combustion,

Limited combustion.

#### Chemical index

Properties	IOTA PDMS	
	47V3	47V10



# 安徽艾约塔硅油有限公司

### IOTA CORPORATION LTD.

安徽省蚌埠市高新区兴中路 985 号 日月科技园

电话: 86-552-3827158 传真: 86-552-3822922

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158
Fax: 86-552-3822922

Appearance	Colorless, transparent liquid	
Viscosity at 25°C, mm2/s, approx.	3	10
Specific gravity at 25°C, approx.	0.890	0.930
Flash point (open cup), °C, approx.	75	182
Freezing point, °C, approx.	-80	-65
Refractive index at 25°C, approx.	1.395	1.399
Surface tension at 25°C,mN/m,	18.9	20.1
approx.		
Vapor pressure at 200℃, Pa,	-	1.33
approx.		
Volume expansion coeff. Between	1.16*	1.08*
25°Cand 100°C, cm³/cm³°C,approx.	10 <sup>-5</sup>	10 <sup>-5</sup>
Specific heat capacity between	-	1.88
40°C and 200°C, J/g, K		
Thermal conductivity, W/mK,	0.11	0.13
approx.		
Viscosity/temperature coeff. [1],	-	0.57
approx.		

[1] Viscosity/temperature coefficient =1- (Viscosity at 99°C/Viscosity at 38°C)

#### **Packaging**

IOTA PDMS 47V3 are available in 20 kg drums.

IOTA PDMS 47V10 are available in 25 and 200 kg drums.

#### Storage and shelf life

When stored in its original unopened packaging at a temperature of between -20 and +30 °C, IOTA PDMS 47V3 - 47V10 may be stored for up to 36 months from its date of



# 安徽艾约塔硅油有限公司

### IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

安徽省蚌埠市高新区兴中路 985 号 日月科技园

电话: 86-552-3827158 传真: 86-552-3822922

manufacture (expiry date). Comply with the storage instructions and expiry date marked on the packaging.

Exceed the date, IOTA Silicones no longer guarantees that the product meets the sales specifications.

### IOTA CORPORATION LTD.

Add: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

TeL: 0086-552-7183958 Fax: 0086-552-3822922

Mobile/What's app/Wechat: 0086-18055289988

Skype: arielyang1988

QQ: 2302519534

Email: info@personalcaresilicone.com

Website: www.personalcaresilicone.com